

Safety Data Sheet

SW1 Lacquer Thinner

Version 1.1

Revision Date: 11/10/2017

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : SW1 Lacquer Thinner

Recommended use of the chemical and restrictions on use

Recommended use : Thinner

Manufacturer or supplier's details

Company : Nexeo Solutions, LLC.
Address : 3 Waterway Square Place Suite 1000
The Woodlands, TX. 77380
United States of America

Emergency telephone number:

Health North America: 1-855-NEXEO4U (1-855-639-3648)

Health International: 1-855-NEXEO4U (1-855-639-3648)

Transport North America: CHEMTREC (1-800-424-9300)

Additional Information: : Responsible Party: Product Safety Group
E-Mail: msds@nexeosolutions.com
SDS Requests: 1-855-429-2661
SDS Requests Fax: 1-281-500-2370
Website: www.nexeosolutions.com

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 2

Skin irritation : Category 2

Eye irritation : Category 2A

Germ cell mutagenicity : Category 1B

Carcinogenicity : Category 2

Reproductive toxicity : Category 2

Specific target organ toxicity
- single exposure : Category 3 (Central nervous system)

Specific target organ toxicity
- repeated exposure : Category 2 (Liver, Kidney, Central nervous system, Auditory system)

Specific target organ toxicity
- repeated exposure (Inhalation)
: Category 2 (Auditory system, Eyes)

Aspiration hazard : Category 1

GHS Label element

Safety Data Sheet SW1 Lacquer Thinner

Version 1.1

Revision Date: 11/10/2017

Hazard pictograms

:



Signal word

: Danger

Hazard statements

: H225 Highly flammable liquid and vapour.
H315 + H320 Causes skin and eye irritation.
H336 May cause drowsiness or dizziness.
H340 May cause genetic defects.
H351 Suspected of causing cancer.
H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

: **Prevention:**
P201 Obtain special instructions before use.
P210 Keep away from open flames/hot surfaces. - No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P242 Use only non-sparking tools.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P281 Use personal protective equipment as required.
Response:
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.
P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P331 Do NOT induce vomiting.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.
Storage:
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up.
Disposal:
P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

The following percentage of the mixture consists of ingredient(s) with unknown acute toxicity: 13.15 %

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Safety Data Sheet

SW1 Lacquer Thinner

Version 1.1

Revision Date: 11/10/2017

Substance / Mixture : Mixture

Hazardous components

CAS-No.	Chemical Name	Weight %
108-88-3	Toluene	50 - 70
67-64-1	Acetone	10 - 20
64742-49-0	Naphtha (petroleum), hydrotreated light	10 - 20
64742-89-8	Solvent naphtha (pet), lt aliph.	10 - 20
68410-97-9	Distillates, pet, lt dist hydrotreat process, low-boil	10 - 20
67-63-0	Isopropyl alcohol	5 - 10
1330-20-7	Mixed xylenes	1 - 5
100-41-4	Ethylbenzene	1 - 5
78-93-3	Methyl ethyl ketone	0.1 - 1
142-82-5	Heptane	0.1 - 1

Any Concentration shown as a range is due to batch variation.

Special Notes: : Functionally equivalent petroleum streams may be found in this preparation at varying concentrations.

SECTION 4. FIRST AID MEASURES

General advice : Show this safety data sheet to the doctor in attendance.
Symptoms of poisoning may appear several hours later.

If inhaled : Consult a physician after significant exposure.

In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
If eye irritation persists, consult a specialist.

If swallowed : Clean mouth with water and drink afterwards plenty of water.
Keep respiratory tract clear.
Do NOT induce vomiting.
Never give anything by mouth to an unconscious person.
Take victim immediately to hospital.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : High volume water jet

Safety Data Sheet

SW1 Lacquer Thinner

Version 1.1

Revision Date: 11/10/2017

Specific hazards during fire-fighting	: Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	: No hazardous combustion products are known
Specific extinguishing methods	: Use a water spray to cool fully closed containers.
Further information	: Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments.
Special protective equipment for firefighters	: Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Environmental precautions	: Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	: Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion	: Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.
Advice on safe handling	: Avoid formation of aerosol. Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8.

Safety Data Sheet

SW1 Lacquer Thinner

Version 1.1

Revision Date: 11/10/2017

Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Container may be opened only under exhaust ventilation hood.
Open drum carefully as content may be under pressure.
Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : No smoking.
Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

CAS-No.	Components	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
108-88-3	Toluene	TWA	20 ppm	ACGIH
		TWA	100 ppm 375 mg/m ³	NIOSH REL
		ST	150 ppm 560 mg/m ³	NIOSH REL
		TWA	200 ppm	OSHA Z-2
		CEIL	300 ppm	OSHA Z-2
		Peak	500 ppm	OSHA Z-2
		TWA	100 ppm 375 mg/m ³	OSHA P0
		STEL	150 ppm 560 mg/m ³	OSHA P0
67-64-1	Acetone	TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
		TWA	250 ppm 590 mg/m ³	NIOSH REL
		TWA	1,000 ppm 2,400 mg/m ³	OSHA Z-1
		TWA	750 ppm 1,800 mg/m ³	OSHA P0
		STEL	1,000 ppm 2,400 mg/m ³	OSHA P0
64742-49-0	Naphtha (petroleum), hydrotreated light	TWA	500 ppm 2,000 mg/m ³	OSHA Z-1
		TWA	400 ppm 1,600 mg/m ³	OSHA P0
64742-89-8	Solvent naphtha (pet), lt aliph.	TWA	500 ppm	OSHA Z-1

Safety Data Sheet

SW1 Lacquer Thinner

Version 1.1

Revision Date: 11/10/2017

			2,000 mg/m3	
		TWA	400 ppm 1,600 mg/m3	OSHA P0
67-63-0	Isopropyl alcohol	TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH
		TWA	400 ppm 980 mg/m3	NIOSH REL
		ST	500 ppm 1,225 mg/m3	NIOSH REL
		TWA	400 ppm 980 mg/m3	OSHA Z-1
		TWA	400 ppm 980 mg/m3	OSHA P0
		STEL	500 ppm 1,225 mg/m3	OSHA P0
1330-20-7	Mixed xylenes	TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH
		TWA	100 ppm 435 mg/m3	OSHA Z-1
		TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH
100-41-4	Ethylbenzene	TWA	20 ppm	ACGIH
		STEL	125 ppm	ACGIH
		TWA	100 ppm 435 mg/m3	NIOSH REL
		ST	125 ppm 545 mg/m3	NIOSH REL
		TWA	100 ppm 435 mg/m3	OSHA Z-1
		TWA	100 ppm 435 mg/m3	OSHA P0
		STEL	125 ppm 545 mg/m3	OSHA P0
78-93-3	Methyl ethyl ketone	TWA	200 ppm	ACGIH
		STEL	300 ppm	ACGIH
		TWA	200 ppm 590 mg/m3	NIOSH REL
		ST	300 ppm 885 mg/m3	NIOSH REL
		TWA	200 ppm 590 mg/m3	OSHA Z-1
		TWA	200 ppm 590 mg/m3	OSHA P0
		STEL	300 ppm 885 mg/m3	OSHA P0
142-82-5	Heptane	TWA	85 ppm 350 mg/m3	NIOSH REL
		C	440 ppm 1,800 mg/m3	NIOSH REL
		TWA	500 ppm 2,000 mg/m3	OSHA Z-1
		TWA	400 ppm 1,600 mg/m3	OSHA P0

Safety Data Sheet

SW1 Lacquer Thinner

Version 1.1

Revision Date: 11/10/2017

		STEL	500 ppm 2,000 mg/m ³	OSHA P0
--	--	------	------------------------------------	---------

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally required.
In the case of vapour formation use a respirator with an approved filter.

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : white

Odour : alcohol-like

Odour Threshold : No data available

pH : No data available

Freezing Point : No data available

Boiling Point (Boiling point/boiling range) : 56 - 142 °C (133 - 288 °F)

Flash point : -16 °C (3 °F)
Method: Tag closed cup

Evaporation rate : 2.1
(Butyl Acetate = 1)

Flammability (solid, gas) : No data available

Upper explosion limit : No data available

Safety Data Sheet

SW1 Lacquer Thinner

Version 1.1

Revision Date: 11/10/2017

Lower explosion limit	: 1.6 %(V)
Vapour pressure	: 60.2 mmHg @ 20 °C (68 °F) 0.9395 PSI @ 20 °C (68 °F)
Relative vapour density	: 2.8(Air = 1.0)
Relative density	: 0.829 @ 20 °C (68 °F) Reference substance: (water = 1)
Density	: No data available
Solubility(ies)	
Water solubility	: soluble
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: 290 °C
Thermal decomposition	: No data available
VOC	: 85.6 % / 707.99 g/l / 5.91 lb/gal
Non VOC	: 14.4 % / 118.81 g/l / 0.99 lb/gal
VOC Vapor Pressure	: 0.8045 PSI
Hazardous Air Pollutants (HAPS)	: 62.0 % / 438.60 g/l / 3.66 lb/gal

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Vapours may form explosive mixture with air.
Conditions to avoid	: temperature extremes Extremes of temperature and direct sunlight. excessive heat Exposure to sunlight.
Incompatible materials	: Avoid contact with: Acids Aldehydes Bases Chlorine Ethylene oxide

Safety Data Sheet SW1 Lacquer Thinner

Version 1.1

Revision Date: 11/10/2017

halogens
isocyanates
metal salts
Oxidizing agents
Reducing agents

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg

Acute inhalation toxicity : Acute toxicity estimate: > 40 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg

Components:

1330-20-7:

Acute inhalation toxicity : LC50 (Rat, male): 6700 ppm
Exposure time: 4 h
Assessment: The component/mixture is moderately toxic after short term inhalation.

Acute dermal toxicity : LD50 (Rabbit): 1,700 mg/kg
Assessment: The component/mixture is moderately toxic after single contact with skin.

100-41-4:

Acute inhalation toxicity : LC50 (Rat, Male): 1432 ppm
Exposure time: 4 h
Assessment: The component/mixture is moderately toxic after short term inhalation.

Skin corrosion/irritation

Components:

108-88-3:

Species: Rabbit
Exposure time: 4 h
Result: Irritating to skin.

64742-49-0:

Species: Rabbit
Result: Irritating to skin.

64742-89-8:

Species: Rabbit

Safety Data Sheet SW1 Lacquer Thinner

Version 1.1

Revision Date: 11/10/2017

Exposure time: 4 h
Result: Irritating to skin.

68410-97-9:
Result: Irritating to skin.

67-63-0:
Species: Rabbit
Result: Irritating to skin.

1330-20-7:
Species: Rabbit
Exposure time: 24 h
Result: Irritating to skin.

142-82-5:
Species: Rabbit
Exposure time: 24 h
Result: Irritating to skin.
Remarks: Based on a similar product formulation.

Serious eye damage/eye irritation

Components:

108-88-3:
Species: Rabbit
Result: Irritating to eyes.

67-64-1:
Species: Rabbit
Result: Irritating to eyes.
Exposure time: 24 h

67-63-0:
Species: Rabbit
Result: Irritating to eyes.

1330-20-7:
Species: Rabbit
Result: Irritating to eyes.

78-93-3:
Species: Rabbit
Result: Irritating to eyes.
Exposure time: 24 h

Germ cell mutagenicity

Components:

108-88-3:
Germ cell mutagenicity - Assessment : Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

64742-89-8:

Safety Data Sheet

SW1 Lacquer Thinner

Version 1.1

Revision Date: 11/10/2017

Germ cell mutagenicity - Assessment : Mutagenicity classification not possible from current data

68410-97-9:

Germ cell mutagenicity - Assessment : Mutagenicity classification not possible from current data

Carcinogenicity

Components:

108-88-3:

Carcinogenicity - Assessment : No evidence of carcinogenicity in animal studies.

64742-89-8:

Carcinogenicity - Assessment : Not classifiable as a human carcinogen.

68410-97-9:

Carcinogenicity - Assessment : Carcinogenicity classification not possible from current data.

IARC

Group 2B: Possibly carcinogenic to humans

64742-49-0 Naphtha (petroleum), hydrotreated light

64742-89-8 Solvent naphtha (pet), lt aliph.

100-41-4 Ethylbenzene

OSHA

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

ACGIH

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

Reproductive toxicity

Components:

108-88-3:

Effects on foetal development : Species: Rat
Application Route: inhalation (vapour)
Dose: 0, 250, 750, 1500, 3000 ppm
Duration of Single Treatment: 10 d
Frequency of Treatment: 6 hr/day
General Toxicity Maternal: NOAEC: 750 ppm
Developmental Toxicity: NOAEC: 750 ppm

Safety Data Sheet

SW1 Lacquer Thinner

Version 1.1

Revision Date: 11/10/2017

Symptoms: Maternal toxicity, Reduced body weight, Skeletal malformations

Teratogenicity - Assessment : Some evidence of adverse effects on development, based on animal experiments.

Reproductive toxicity - Assessment : No toxicity to reproduction

64742-89-8:

Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility, based on animal experiments.

Teratogenicity - Assessment : Embryotoxicity classification not possible from current data.

68410-97-9:

Teratogenicity - Assessment : Some evidence of adverse effects on development, based on animal experiments.

STOT - single exposure

Components:

108-88-3:

Exposure routes: Inhalation

Target Organs: Central nervous system

Assessment: May cause drowsiness or dizziness., The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

67-64-1:

Exposure routes: Inhalation

Target Organs: Central nervous system

Assessment: May cause drowsiness or dizziness., The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

64742-49-0:

Target Organs: Central nervous system

Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

64742-89-8:

Target Organs: Central nervous system

Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

68410-97-9:

Target Organs: Central nervous system

Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

Safety Data Sheet

SW1 Lacquer Thinner

Version 1.1

Revision Date: 11/10/2017

67-63-0:

Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

78-93-3:

Target Organs: Central nervous system

Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

142-82-5:

Target Organs: Central nervous system

Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

STOT - repeated exposure

Components:

108-88-3:

Exposure routes: Inhalation

Target Organs: Auditory system, Eyes

Assessment: May cause damage to organs through prolonged or repeated exposure., The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

100-41-4:

Target Organs: Auditory system

Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

Aspiration toxicity

Components:

108-88-3:

May be fatal if swallowed and enters airways.

64742-49-0:

Aspiration Toxicity - Category 1

64742-89-8:

May be fatal if swallowed and enters airways.

68410-97-9:

May be fatal if swallowed and enters airways.

100-41-4:

May be fatal if swallowed and enters airways.

142-82-5:

May be fatal if swallowed and enters airways.

Further information

Product:

Safety Data Sheet

SW1 Lacquer Thinner

Version 1.1

Revision Date: 11/10/2017

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.
Concentrations substantially above the TLV value may cause narcotic effects.
Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

108-88-3:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 5.5 mg/l
Exposure time: 96 h
Test Type: flow-through test

Toxicity to daphnia and other aquatic invertebrates : LC50 (Ceriodaphnia dubia): 3.78 mg/l
Exposure time: 48 h
Test Type: Renewal

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0.74 mg/l
Exposure time: 7 d

Acute aquatic toxicity- Assessment : Toxic to aquatic life.

Chronic aquatic toxicity- Assessment : Harmful to aquatic life with long lasting effects.

64742-49-0:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 10 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 4.5 mg/l
Exposure time: 48 h

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): 3.71 mg/l
Exposure time: 96 h

Chronic aquatic toxicity- Assessment : Toxic to aquatic life with long lasting effects.

64742-89-8:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 8.2 mg/l
Exposure time: 96 h
Test Type: semi-static test

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 4.5 mg/l
Exposure time: 48 h
Test Type: Immobilization

Safety Data Sheet

SW1 Lacquer Thinner

Version 1.1

Revision Date: 11/10/2017

Toxicity to algae	: EC50 (Pseudokirchneriella subcapitata (green algae)): 3.7 mg/l Exposure time: 96 h Test Type: static test
Chronic aquatic toxicity- Assessment	: Toxic to aquatic life with long lasting effects.
68410-97-9:	
Toxicity to fish	: LC50 (Pimephales promelas (fathead minnow)): 8.2 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): 4.5 mg/l Exposure time: 48 h
Toxicity to algae	: EC50 (Pseudokirchneriella subcapitata (green algae)): 3.1 mg/l Exposure time: 72 h
Toxicity to fish (Chronic toxicity)	: NOELR (Pimephales promelas (fathead minnow)): 2.6 mg/l Exposure time: 14 d
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOELR (Daphnia magna (Water flea)): 2.6 mg/l Exposure time: 21 d
Chronic aquatic toxicity- Assessment	: Toxic to aquatic life with long lasting effects.
100-41-4:	
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): 1.8 mg/l Exposure time: 48 h Test Type: static test
Toxicity to algae	: EC50 (Pseudokirchneriella subcapitata (microalgae)): 5.4 mg/l Exposure time: 72 h Test Type: static test
Chronic aquatic toxicity- Assessment	: Harmful to aquatic life with long lasting effects.
142-82-5:	
Toxicity to fish	: LC50 (Carassius auratus (goldfish)): 4 mg/l Exposure time: 24 h
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): 1.5 mg/l Exposure time: 48 h Test Type: static test
Toxicity to fish (Chronic toxicity)	: NOELR (Oncorhynchus mykiss (rainbow trout)): 1.284 mg/l Exposure time: 28 d
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (Daphnia magna (Water flea)): 0.17 mg/l Exposure time: 21 d

Safety Data Sheet

SW1 Lacquer Thinner

Version 1.1

Revision Date: 11/10/2017

Acute aquatic toxicity- Assessment : Very toxic to aquatic life.

Chronic aquatic toxicity- Assessment : Very toxic to aquatic life with long lasting effects.

Persistence and degradability

No data available

Bioaccumulative potential

Components:

108-88-3:

Partition coefficient: n-octanol/water : log Pow: 2.73 (20 °C)
pH: 7

Mobility in soil

No data available

Other adverse effects

Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Toxic to aquatic life with long lasting effects.

Components:

100-41-4:

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with all applicable local, state and federal regulations.
For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact NEXEO's Environmental Services Group at 800-637-7922.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

Safety Data Sheet

SW1 Lacquer Thinner

Version 1.1

Revision Date: 11/10/2017

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

DOT (Department of Transportation):

UN1263, PAINT RELATED MATERIAL, 3, II

IATA (International Air Transport Association):

UN1263, PAINT RELATED MATERIAL, 3, II

IMDG (International Maritime Dangerous Goods):

UN1263, PAINT RELATED MATERIAL, 3, II, Flash Point:-16 °C(3 °F)

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Toluene	108-88-3	1000	1701

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards

: Fire Hazard
Chronic Health Hazard
Acute Health Hazard

Clean Air Act

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

108-88-3	Toluene
100-41-4	Ethylbenzene
71-43-2	Benzene
110-54-3	Hexane
67-56-1	Methanol
98-82-8	Cumene
91-20-3	Naphthalene

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCMII Intermediate or Final VOC's (40 CFR 60.489):

108-88-3	Toluene
67-64-1	Acetone
67-63-0	Isopropyl alcohol
1330-20-7	Mixed xylenes
100-41-4	Ethylbenzene
78-93-3	Methyl ethyl ketone
110-82-7	Cyclohexane

Safety Data Sheet

SW1 Lacquer Thinner

Version 1.1

Revision Date: 11/10/2017

71-43-2	Benzene
64-17-5	Ethanol
71-23-8	n-Propanol
67-56-1	Methanol
98-82-8	Cumene

Clean Water Act

The following Hazardous Substances are listed under the U.S. CleanWater Act, Section 311, Table 116.4A:

108-88-3	Toluene
1330-20-7	Mixed xylenes
100-41-4	Ethylbenzene
110-82-7	Cyclohexane
71-43-2	Benzene
91-20-3	Naphthalene

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

108-88-3	Toluene
1330-20-7	Mixed xylenes
100-41-4	Ethylbenzene
110-82-7	Cyclohexane
71-43-2	Benzene
91-20-3	Naphthalene

This product contains the following toxic pollutants listed under the U.S. Clean Water Act Section 307

108-88-3	Toluene
100-41-4	Ethylbenzene

US State Regulations

Massachusetts Right To Know

108-88-3	Toluene	50 - 70 %
67-64-1	Acetone	10 - 20 %
67-63-0	Isopropyl alcohol	5 - 10 %
1330-20-7	Mixed xylenes	1 - 5 %
100-41-4	Ethylbenzene	1 - 5 %
71-43-2	Benzene	0 - 0.1 %

Pennsylvania Right To Know

108-88-3	Toluene	50 - 70 %
67-64-1	Acetone	10 - 20 %
64742-49-0	Naphtha (petroleum), hydrotreated light	10 - 20 %
64742-89-8	Solvent naphtha (pet), lt aliph.	10 - 20 %
68410-97-9	Distillates, pet, lt dist hydrotreat process, low-boil	10 - 20 %
67-63-0	Isopropyl alcohol	5 - 10 %
1330-20-7	Mixed xylenes	1 - 5 %
100-41-4	Ethylbenzene	1 - 5 %
78-93-3	Methyl ethyl ketone	0.1 - 1 %
110-82-7	Cyclohexane	0.1 - 1 %
71-43-2	Benzene	0 - 0.1 %

New Jersey Right To Know

108-88-3	Toluene	50 - 70 %
67-64-1	Acetone	10 - 20 %
64742-49-0	Naphtha (petroleum), hydrotreated light	10 - 20 %

Safety Data Sheet

SW1 Lacquer Thinner

Version 1.1

Revision Date: 11/10/2017

64742-89-8	Solvent naphtha (pet), lt aliph.	10 - 20 %
68410-97-9	Distillates, pet, lt dist hydrotreat process, low-boil	10 - 20 %
67-63-0	Isopropyl alcohol	5 - 10 %
1330-20-7	Mixed xylenes	1 - 5 %
100-41-4	Ethylbenzene	1 - 5 %

California Prop 65

	WARNING! This product contains a chemical known to the State of California to cause cancer.	
100-41-4	Ethylbenzene	
71-43-2	Benzene	
98-82-8	Cumene	
91-20-3	Naphthalene	
	WARNING! This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.	
108-88-3	Toluene	
71-43-2	Benzene	
67-56-1	Methanol	

The components of this product are reported in the following inventories:

TSCA	: On TSCA Inventory
DSL	: All components of this product are on the Canadian DSL
AICS	: On the inventory, or in compliance with the inventory
NZIoC	: Not in compliance with the inventory
ENCS	: Not in compliance with the inventory
KECI	: On the inventory, or in compliance with the inventory
PICCS	: On the inventory, or in compliance with the inventory
IECSC	: On the inventory, or in compliance with the inventory


Safety Data Sheet SW1 Lacquer Thinner

Version 1.1

Revision Date: 11/10/2017

SECTION 16. OTHER INFORMATION

NFPA:



HMIS III:

HEALTH	2*
FLAMMABILITY	3
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

The information accumulated is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made become available subsequently to the date hereof, we do not assume any responsibility for the results of its use. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This MSDS has been prepared by NEXEO™ Solutions EHS Product Safety Department (1-855-429-2661) MSDS@nexeosolutions.com.

Revision Date : 11/10/2017

Material number:

16056645, 16061967, 16056647, 16056646, 16056648

Key or legend to abbreviations and acronyms used in the safety data sheet			
ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic

Safety Data Sheet

SW1 Lacquer Thinner

Version 1.1

Revision Date: 11/10/2017

GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%		